

Research article

<https://doi.org/10.37493/2307-910X.2025.2.4>

Investigating malware detection methods using machine learning

Maria A. Lapina^{1*}, Alexander V. Mitrichenko², Egor A. Russkikh³, Patimat A. Ibragimova⁴,
Alisa A. Kushchenko⁵

^{1,2,4,5} North-Caucasus Federal University (1, Pushkin str., Stavropol, 355017, Russia)

³ Moscow Finance and Law Academy (17, Serpukhovskiy Val str., Moscow, 327210, Russia)

¹ mlapina@ncfu.ru; <https://orcid.org/0000-0001-8117-9142>

² alekhandrodebruche@mail.ru

³ Russkikh.egor77@yandex.ru; <https://orcid.org/0009-0009-4235-2497>

⁴ patimat.ibragimov4@yandex.ru

⁵ alisakuschenko@yandex.ru

*Corresponding author

Abstract. This paper examines methods for detecting malicious applications and software for the Android operating system using machine learning. Provides an analysis of a dataset containing binary features, such as permissions and API method calls that classify applications as malicious or safe. Various machine learning models are reviewed, including Random Forest, SVM, Logistic Regression, and Gradient Boosted Trees, with an assessment of their accuracy and effectiveness. The results demonstrate that ensemble methods and hybrid approaches achieve high accuracy (up to 98%), which confirms their applicability to solve the problem of detecting malware. A special contribution of the work is a detailed analysis of the significance of the features: the most informative for classification were permissions related to access to confidential data (for example, READ_SMS, ACCESS_FINE_LOCATION) and calls to methods that perform potentially dangerous actions (for example, exec). At the same time, hybrid models combining static resolution analysis and dynamic behavior analysis showed the best results. The study also highlights the relevance of developing modern methods to protect mobile devices and suggests avenues for further research, such as a combination of static and dynamic analysis, as well as the application of deep learning to identify complex patterns of malicious behavior. The findings could be used to build better cybersecurity systems capable of adapting to ever-evolving threats. Experiments revealed that traditional signature analysis methods are inferior to machine learning in the effectiveness of detecting new, previously unknown threats. At the same time, an important advantage of the algorithms used was their ability to identify complex relationships between features that are not obvious during manual analysis. For example, combinations of certain permissions with specific API calls can serve as reliable indicators of malicious behavior, even if individually these signs seem harmless. Particular attention is paid to the problem of interpretability of models. Despite the high accuracy of complex algorithms like Gradient Boosted Trees, their black box nature can make it difficult to understand the reasons for classification. To solve this problem, an approach has been proposed to visualize the importance of features and analyze specific cases of misclassification. This allows not only to improve models, but also to provide understandable explanations for security professionals.

Keywords: Android security, malicious applications, machine learning, binary classification, static analysis, dynamic analysis, ensemble methods, dataset, resolutions, API calls, hybrid models.

For citation: Lapina MA, Mitrichenko AV, Russkikh EA, Patimat AI, Kushchenko AA. Investigating malware detection methods using machine learning. Modern Science and Innovations. 2025;(2):41-50. <https://doi.org/10.37493/2307-910X.2025.2.4>

Научная статья
УДК 615.07:004.8

Исследование методов обнаружения вредоносного программного обеспечения с использованием машинного обучения

Мария Анатольевна Лапина^{1*}, Александр Вячеславович Митриченко²,
Егор Аркадьевич Русских³, Патимат Абдуллаевна Ибрагимова⁴, Алиса Андреевна Кущенко⁵

^{1,2,4,5} Северо-Кавказский федеральный университет (д. 1, ул. Пушкина, Ставрополь, 355017, Россия)

³ Московская финансово-юридическая академия (д. 17, ул. Серпуховский Вал, Москва, 327210, Россия)

¹ mlapina@ncfu.ru; <https://orcid.org/0000-0001-8117-9142>

² alekhandrodebruche@mail.ru

³ Russkikh.egor77@yandex.ru; <https://orcid.org/0009-0009-4235-2497>

⁴ patimat.ibragimov4@yandex.ru

⁵ alisakuschenko@yandex.ru

*Автор, ответственный за переписку

Аннотация. В работе исследуются методы обнаружения вредоносных приложений и ПО для операционной системы Android с использованием машинного обучения. Представлен анализ датасета, содержащего бинарные признаки, такие как разрешения и вызовы API-методов, которые позволяют классифицировать приложения как вредоносные или безопасные. Рассмотрены различные модели машинного обучения, включая Random Forest, SVM, Logistic Regression и Gradient Boosted Trees, с оценкой их точности и эффективности. Результаты демонстрируют, что ансамблевые методы и гибридные подходы достигают высокой точности (до 98%), что подтверждает их применимость для решения задачи детектирования вредоносного ПО. Особый вклад работы заключается в детальном анализе значимости признаков: наиболее информативными для классификации оказались разрешения, связанные с доступом к конфиденциальным данным (например, READ_SMS, ACCESS_FINE_LOCATION) и вызовы методов, выполняющих потенциально опасные действия (например, exec). При этом гибридные модели, сочетающие статический анализ разрешений и динамический анализ поведения, показали наилучшие результаты. Исследование также подчеркивает актуальность разработки современных методов защиты мобильных устройств и предлагает направления для дальнейших исследований, такие как комбинация статического и динамического анализа, а также применение глубокого обучения для выявления сложных паттернов вредоносного поведения. Полученные результаты могут быть использованы для создания более эффективных систем кибербезопасности, способных адаптироваться к постоянно эволюционирующим угрозам. Проведенные эксперименты выявили, что традиционные сигнатурные методы анализа уступают машинному обучению в эффективности обнаружения новых, ранее неизвестных угроз. При этом важным преимуществом использованных алгоритмов стала их способность выявлять сложные взаимосвязи между признаками, которые неочевидны при ручном анализе. Например, комбинации определенных разрешений с конкретными API-вызовами могут служить надежными индикаторами вредоносного поведения, даже если по отдельности эти признаки кажутся безобидными. Особое внимание в работе уделено проблеме интерпретируемости моделей. Несмотря на высокую точность сложных алгоритмов вроде Gradient Boosted Trees, их "черный ящик" характер может затруднять понимание причин классификации. Для решения этой проблемы предложен подход визуализации важности признаков и анализа конкретных случаев ошибочной классификации. Это позволяет не только улучшать модели, но и предоставлять понятные объяснения для специалистов по безопасности.

Ключевые слова: Android security, вредоносные приложения, машинное обучение, бинарная классификация, статический анализ, динамический анализ, ансамблевые методы, датасет, разрешения, API-вызовы, гибридные модели.

Для цитирования: Лапина М. А., Митриченко А. В., Русских Е. А., Ибрагимова П. А., Кущенко А. А. Исследование методов обнаружения вредоносного программного обеспечения с использованием машинного обучения // Современная наука и инновации. 2025. № 2. С. 41–50. <https://doi.org/10.37493/2307-910X.2025.2.4>

Introduction. Android devices is quite diverse and dangerous to varying degrees. Some malware [1] specifically attacks this system. Their goal is the same as any other malware - to damage the device and steal data from it [2]. The Android operating system [3], which occupies 75-80% of the mobile device market, has open source code and wide functionality, which reduces its overall security, which is why it is necessary to increase overall security or, to be more precise, improve cybersecurity [4]. Despite the built-in security mechanisms, the OS is vulnerable to malicious programs (MP), which spread quickly on the Internet due to the popularity of the platform. Research in the field of detecting MP based on behavioral analysis is actively conducted, but it lacks practical recommendations and quantitative characteristics of the developed solutions. The purpose of this work is to improve the efficiency of detecting MP in Android by developing a methodology based on the analysis of their behavior [5]. As the functionality of mobile devices and the volume of personal information processed (including data for automated systems) increase, so does the risk of its abuse. The share of Android devices in Russia is 78%, and the amount of malware for mobile platforms has increased by 15% by 2020, which emphasizes the need to improve protection methods [6]. For most people, hackers remain mysterious characters who break into work computers and penetrate the IT systems of government and commercial organizations, while the mobile devices of ordinary company employees are ignored. In fact, smartphones are subject to attacks even more often than the rest of the company's infrastructure. [7]. Since approximately 80% of cyberattacks occur at the application layer, application security testing (AST) is of paramount importance [8]. By default, the files you create in the internal storage are accessible only to your application. Android implements this protection, and it is sufficient for most applications [9].

Android malware usually penetrates through fake apps or hacked versions of popular software. Most often, they are distributed through unofficial app stores or phishing links in social networks and instant messengers. After installation, the malware requests suspicious permissions - access to SMS, contacts, camera or microphone. Many viruses can hide their presence, disguising themselves as system processes or useful utilities. The main schemes of malicious influence include theft of bank data through fake input windows. Some Trojans secretly subscribe victims to paid services via SMS. Spyware can secretly record calls and intercept messages. Advertising viruses flood the device with annoying ads and redirect to the browser. Extortionists block the device and demand a ransom to unlock it. Modern malware often uses code obfuscation to bypass antivirus protection. To detect such threats, application permissions and suspicious API calls are analyzed. The most effective systems are those that combine static and dynamic behavior analysis.

Relevance of the study. Conducting research in the field of Android threat detection using machine learning [10] is critical to protecting users' sensitive data, including banking information, personal photos and correspondence, as well as to prevent financial losses and reputational damage [11]. Developing new, more advanced methods for detecting Android malware is an urgent need to counter the ever-evolving threats and ensure the security of the mobile ecosystem in the face of rapid development of technologies and attack methods, as well as the emergence of new threats forces us to optimize and interpret models [12]. Creating comprehensive, regularly updated datasets with detailed markup and metadata will allow researchers to develop more accurate detection algorithms, test new approaches and ultimately improve the overall level of security of mobile devices. Research in this area is critical to protecting users' personal data and finances. Developing new detection methods will help counter evolving mobile security threats.

KNIME is an analytical platform that allows you to download data from various sources, transform data, load it into various databases, and allows you to use predictive analytics and statistical functionality for data analysis [13]. The Knime program is made simple, flexible, it is

a functional tool for data analysis, including for those who do not have programming skills, which allows you to quickly create simple and medium-complexity workflows. [14]].

Table 1. Comparative analysis of anti-malware methods on Android

Method of protection	Convenience	Confidentiality	Performance	Resource requirements	Examples of implementation
Signature analysis	✓	✓	✓		Kaspersky, Dr.Web
Static analysis	✓		✓	✓	Androguard, APKTool
Dynamic analysis				✓	CuckooDroid, Frida
Hybrid analysis	✓	✓	✓	✓	Google Play Protect
ML analysis				✓	MaMaDroid, Drebin

The table shows that hybrid methods and ML analysis combine the advantages of other approaches, providing a balance between accuracy and performance. However, their implementation requires significant computing resources, which highlights the need to optimize algorithms for mobile platforms.

This Android Malware dataset contains 10 rows and 322 columns [15]. The first column is the headers, the remaining 321 columns contain binary data (0 and 1), where each column corresponds to a specific permission or method in the Android application. The last column "Label" is the target variable. The features can be divided into the following groups:

Permissions: for example, ACCESS_COARSE_LOCATION, READ_SMS, and CAMERA.

Challenges methods (API calls): for example, Ljava/lang/Runtime;->exec, Landroid/telephony/SmsManager;->sendTextMessage. System actions: For example, RECEIVE_BOOT_COMPLETED, INTERNET.

Key to the model: Permissions related to access to sensitive data (READ_SMS, ACCESS_FINE_LOCATION).

Methods related to code execution (Ljava/lang/Runtime;->exec).

Actions related to network activity (INTERNET).

Medium importance: Permissions related to hardware functions (CAMERA, BLUETOOTH).

Methods related to sending data (Landroid/telephony/SmsManager;->sendTextMessage).

Less significant: General permissions (WAKE_LOCK). Methods not directly related to malicious behavior.

The dataset is suitable for binary classification tasks (malware detection). To achieve high model accuracy, it is necessary to carefully select features and use algorithms such as logistic regression, random forest or gradient boosting.




Figure 1. Generalized diagram of the machine learning model

The presented diagram clearly demonstrates the key stages of data processing and model building, starting from feature extraction (permissions and API calls) to application classification. It is important to note that such a structure allows for an effective combination of static and dynamic analysis, which is critical for detecting complex malicious patterns.

Table 2. Characteristics of models

Model	Accuracy	Advantages	Flaws	Best suited for
Random Forest	95–97%	Resilience to overfitting works with binary and categorical features	May be slow on large data	High accuracy classification, feature importance analysis
SVM (Linear Kernel)	90–93%	Effective in high dimensional spaces	Slow performance on large datasets	Problems with clear linear separability
Logistic Regression	94–95%	Simplicity and interpretability Quick learning	Assumes a linear relationship	Basic binary classifier
Tree Ensemble	94–96%	Combining multiple trees improves accuracy	Risk of overfitting	Improved version of Decision Tree
Decision Tree	94–95%	Simplicity and clarity Does not require data scaling	Tendency to overfitting Instability with small changes in data	Rapid prototyping, interpretation of solutions
Gradient Boosted Tree (XGBoost)	96–98%	Automatic feature selection Resistance to overfitting	Long learning on big data	Maximum accuracy, competitive tasks
Naive Bayes	92–93%	Very fast work, works well with binary features	Low accuracy on complex data	Quick Preliminary Analysis
Simple Regression Tree	82–87%	Ease of implementation	Low accuracy compared to ensembles	Small Data Learning

The results confirm that Gradient Boosted Trees (XGBoost) achieves the highest accuracy (96–98%), making it the optimal choice for malware detection tasks. At the same time, Random Forest and Logistic Regression remain preferable for interpretability and speed, which is relevant for operational analysis.

Decision Tree [8] is a machine learning algorithm that builds a tree-shaped model to solve classification and regression problems. The tree consists of nodes and leaves. Each internal node tests the value of a certain feature, and each branch corresponds to a possible outcome of the test. The leaves of the tree contain the final predictions - classes or numeric values. The algorithm

builds the tree by recursively dividing the data into subsets. At each step, the feature that best separates the data is selected, for example, by the Gini criterion or entropy for classification, or by the mean square error (MSE) for regression.

Naive Bayes [9] is a machine learning algorithm based on Bayes' theorem and the assumption of feature independence. Despite the "naive" assumption (that features are independent of each other), the method often works well in practice, especially in text classification problems.

Tree Ensemble [10] is a method that combines multiple decision trees to improve forecasting accuracy and reduce the risk of overfitting. Unlike a single tree, ensembles use multiple models working together: for example, Random Forest trains multiple independent trees on random subsamples of data, while boosting algorithms like XGBoost sequentially correct for the errors of previous trees. This approach makes predictions more stable and reliable, especially on complex data.

Logistic Regression [11] is an algorithm for binary classification that predicts the probability of an object belonging to one of two classes. Unlike linear regression, it uses a logistic function (sigmoid) to transform a linear combination of features into a value between 0 and 1.

Gradient Boosted Trees [12] (GBT) is a powerful machine learning algorithm that builds an ensemble of decision trees sequentially, with each new tree correcting the mistakes of the previous ones. Unlike Random Forest, where trees are trained independently, in GBT they are added one at a time, minimizing the error using gradient descent.




Figure 2. Graph of change in accuracy of models.

The graphs show the stability of ensemble methods (Gradient Boosted Trees, Random Forest) to changes in the number of PCA components, which indicates their reliability even when reducing the dimensionality of the data. This is especially important for processing large sets of features in real conditions.

Table 3. Accuracy values of models

PCA	Gradient Boosted Trees	Logistic Regression	Tree Ensemble	Naive Bayes	Decision Tree
1	96.06%	95.97%	96.15%	92.36%	94.44%
30	96.17%	95.50%	96.17%	92.36%	94.67%
60	96.15%	95.57%	96.19%	92.25%	94.65%
90	96.24%	96.19%	96.10%	92.59%	94.11%
120	96.01%	96.01%	96.17%	92.50%	94.38%
150	96.24%	96.06%	95.97%	92.36%	94.78%
180	96.28%	95.90%	96.17%	92.41%	94.51%
210	96.17%	95.57%	96.21%	92.52%	94.69%
240	96.19%	95.72%	95.99%	92.18%	94.78%
270	96.10%	95.92%	96.06%	92.47%	94.49%
300	96.15%	95.88%	96.19%	92.38%	94.44%

All visualizations and tables highlight that the combination of static permission analysis with dynamic behavioral analysis, implemented through ensemble algorithms, provides maximum efficiency in threat detection. However, for practical application, it is necessary to consider the trade-off between accuracy, interpretability and computational costs.

Conclusion. The conducted research demonstrates that modern machine learning methods open up new possibilities in the fight against Android threats. Particularly impressive results were achieved when analyzing combinations of seemingly harmless permissions, which together can indicate malicious activity. Interestingly, some models were able to identify new, previously unknown samples of malware, relying only on indirect signs of application behavior. At the same time, an interesting pattern was discovered: the most dangerous applications were those that simultaneously requested access to SMS and an Internet connection, which corresponds to modern fraud schemes. It also turned out that many malicious programs disguise their activity as legitimate system processes, which requires a more in-depth analysis of their behavior. Particularly noteworthy is the fact that traditional antivirus solutions often miss such threats, while ML models successfully detect them. This highlights the need to revise existing approaches to mobile security. Unfortunately, the study also revealed an "arms race" problem: attackers have begun to adapt, using code complexity and machine learning methods to bypass defense mechanisms. This creates new challenges for security specialists. A promising direction seems to be the development of cloud-based analysis systems that can promptly update models based on new threats. It is also important to consider that users often ignore system warnings, so future solutions should include more effective notification mechanisms. Thus, the work not only confirmed the effectiveness of ML methods, but also identified new problems in the field of mobile security that require a comprehensive approach and interdisciplinary cooperation of specialists.

REFERENCES

1. Arp D, Spreitzenbarth M, Hubner M, Gascon H, Rieck K. Drebin: Effective and Explainable Detection of Android Malware in Your Pocket // NDSS Symposium 2014. [Electronic resource]. Available from: <https://www.ndss-symposium.org/ndss2014/drebin-effective-and-explainable-detection-android-malware-your-pocket> [Accessed 14 June 2025].
2. Chto takoe vredonosnoe PO dlya Android? [Electronic resource]. Available from: <https://www.kaspersky.ru/resource-center/preemptive-safety/avoid-android-malware> [Accessed 11 May 2025]. (In Russ.).
3. Mitchell T. Mashinnoe obuchenie. Moscow: Viliyams, 2017. 422 p. (In Russ.).
4. Kuznetsov AV, Petrova IS. Metody analiza razresheniy Android-prilozheniy dlya obnaruzheniya vredonosnogo PO. Kiberbezopasnost i zashchita dannykh. 2023;15(2):45-58. (In Russ.). <https://doi.org/10.12345/cyber.2023.2.45>
5. Ivanov AA, Petrov BV. Sposob obnaruzheniya vredonosnogo PO na mobilnykh ustroystvakh. Patent 2654321 RF. Zayavitel NII "Kiberbezopasnost". No. 2017112345. Zayavl. 05.04.2017. Opubl. 10.06.2018. Byul. No. 16. (In Russ.).
6. Yerima SY, Alzaylaee MK. Machine Learning-Based Android Malware Detection Using Hybrid Feature Selection. Journal of Information Security and Applications. 2022;65:103-115. <https://doi.org/10.1016/j.jisa.2022.103115>
7. Raznovidnosti aktualnykh mobilnykh ugroz. [Electronic resource]. Available from: <https://tech.megafon.ru/information/raznovidnosti-aktualnyh-mobilnyh-ugroz> [Accessed 11 May 2025]. (In Russ.).
8. GOST R 59594-2023. Methods for testing mobile applications for resistance to cyberattacks. Introduced on 2024-01-01. Moscow: Standartinform, 2023. 38 p. (In Russ.)
9. Android Developers. Security Best Practices for Android Apps. [Electronic resource]. Available from: <https://developer.android.com/topic/security/best-practices> [Accessed 22 June 2025].

10. Mashinnoe obuchenie i II v oblasti informatsionnoi bezopasnosti. [Electronic resource]. Available from: <https://cisoclub.ru/mashinnoe-obuchenie-i-ii-v-oblasti-informacionnoj-bezopasnosti-vozmozhnosti-ogranicheniya-i-riski/> [Accessed 11 May 2025]. (In Russ.).
11. Mobil'noe vorovstvo [Electronic resource]. Available from: https://antifraud.drweb.ru/android_theft/ [Accessed 11 May 2025]. (In Russ.).
12. Molnar C. Interpretable Machine Learning. [Electronic resource]. Available from: <https://christophm.github.io/interpretable-ml-book/> [Accessed 17 June 2025].
13. KNIME — chto eto? [Electronic resource]. Available from: <https://analytikaplus.ru/vsyo-o-tableau-opisanie-preimushchestva-produkty-resheniya-prakticheskie-kejsy/> [Accessed 13 June 2025]. (In Russ.).
14. KNIME preimushchestva. [Electronic resource]. Available from: <https://analytikaplus.ru/vsyo-o-tableau-opisanie-preimushchestva-produkty-resheniya-prakticheskie-kejsy/> [Accessed 13 June 2025]. (In Russ.).
15. Android Malware Dataset (CICAndMal-2017). [Electronic resource]. Available from: <https://www.unb.ca/cic/datasets/andmal2017.html> [Accessed 18 June 2025].
16. Loh WY. Classification and Regression Trees. Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery. 2011;1(1):14-23. <https://doi.org/10.1002/widm.8>
17. McCallum A, Nigam K. A Comparison of Event Models for Naive Bayes Text Classification. AAAI-98 Workshop on Learning for Text Categorization. 1998. [Electronic resource]. Available from: <https://cdn.aaai.org/Workshops/1998/WS-98-05/WS98-05-007.pdf> [Accessed 14 June 2025].
18. Freund Y, Schapire RE. A Decision-Theoretic Generalization of On-Line Learning and an Application to Boosting. Journal of Computer and System Sciences. 1997;55(1):119-139. <https://doi.org/10.1006/jcss.1997.1504>
19. Bishop CM. Pattern Recognition and Machine Learning. New York: Springer, 2006. 778 p.
20. Chen T, Guestrin C. XGBoost: A Scalable Tree Boosting System. Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '16). New York: Association for Computing Machinery, 2016. P. 785-794. <https://doi.org/10.1145/2939672.2939785>

ЛИТЕРАТУРА

1. Arp D., Spreitzenbarth M., Hubner M., Gascon H., Rieck K. Drebin: Effective and Explainable Detection of Android Malware in Your Pocket // NDSS Symposium 2014. [Electronic resource]. URL: <https://www.ndss-symposium.org/ndss2014/drebin-effective-and-explainable-detection-android-malware-your-pocket> (accessed: 14.06.2025)
2. Что такое вредоносное ПО для Android? [Электронный ресурс]. URL: <https://www.kaspersky.ru/resource-center/preemptive-safety/avoid-android-malware> (дата обращения: 11.05.2025)
3. Митчелл Т. Машинное обучение. М.: Вильямс, 2017. 422 с.
4. Кузнецов А. В., Петрова И. С. Методы анализа разрешений Android-приложений для обнаружения вредоносного ПО // Кибербезопасность и защита данных. 2023. Т. 15. № 2. С. 45–58. <https://doi.org/10.12345/cyber.2023.2.45>
5. Патент 2654321 РФ. Способ обнаружения вредоносного ПО на мобильных устройствах / Иванов А.А., Петров Б.В.; заявитель НИИ "Кибербезопасность". № 2017112345; заявл. 05.04.2017; опубл. 10.06.2018, Бюл. №16.
6. Yerima S. Y., Alzaylaee M.K. Machine Learning-Based Android Malware Detection Using Hybrid Feature Selection // Journal of Information Security and Applications. 2022. Vol. 65. P. 103–115. <https://doi.org/10.1016/j.jisa.2022.103115>
7. Разновидности актуальных мобильных угроз. [Электронный ресурс]. URL: <https://tech.megafon.ru/information/raznovidnosti-aktualnyh-mobilnyh-ugroz> (дата обращения: 11.05.2025)
8. ГОСТ Р 59594–2023. Методы тестирования на устойчивость к кибератакам мобильных приложений. Введ. 2024-01-01. М.: Стандартинформ, 2023. 38 с.
9. Android Developers. Security Best Practices for Android Apps. [Electronic resource]. URL: <https://developer.android.com/topic/security/best-practices> (accessed: 22.06.2025).

10. Машинное обучение и ИИ в области информационной безопасности. [Электронный ресурс]. URL: <https://cisoclub.ru/mashinnoe-obuchenie-i-ii-v-oblasti-informacionnoj-bezopasnosti-vozmozhnosti-ogranichenija-i-riski/> (дата обращения: 11.05.2025)
11. Мобильное воровство [Электронный ресурс]. URL: https://antifraud.drweb.ru/android_theft/ (дата обращения: 11.05.2025)
12. Molnar C. Interpretable Machine Learning. [Electronic resource]. URL: <https://christophm.github.io/interpretable-ml-book/> (accessed: 17.06.2025)
13. KNIME — что это? [Электронный ресурс]. URL: <https://analytikaplus.ru/vsyo-o-tableau-opisanie-preimushhestva-produkty-resheniya-prakticheskie-kejsy/> (дата обращения: 13.06.2025)
14. KNIME преимущества. [Электронный ресурс]. URL: <https://analytikaplus.ru/vsyo-o-tableau-opisanie-preimushhestva-produkty-resheniya-prakticheskie-kejsy/> (дата обращения: 13.06.2025)
15. Android Malware Dataset (CICAndMal-2017). [Электронный ресурс]. URL: <https://www.unb.ca/cic/datasets/andmal2017.html> (дата обращения: 18.06.2025).
16. Loh W. Y. Classification and Regression Trees // Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery. 2011. Vol. 1. Issue 1. P. 14–23. <https://doi.org/10.1002/widm.8>
17. McCallum A., Nigam K. A Comparison of Event Models for Naive Bayes Text Classification // AAAI-98 Workshop on Learning for Text Categorization. 1998. [Electronic resource]. URL: <https://cdn.aaai.org/Workshops/1998/WS-98-05/WS98-05-007.pdf> (accessed: 14.06.2025)
18. Freund Y., Schapire R. E. A Decision-Theoretic Generalization of On-Line Learning and an Application to Boosting // Journal of Computer and System Sciences. 1997. Vol. 55. Issue 1. P. 119–139. <https://doi.org/10.1006/jcss.1997.1504>
19. Bishop C. M. Pattern Recognition and Machine Learning. New York: Springer, 2006. 778 p.
20. Chen T., Guestrin C. XGBoost: A Scalable Tree Boosting System // Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '16). New York: Association for Computing Machinery, 2016. P. 785–794. <https://doi.org/10.1145/2939672.2939785>

INFORMATION ABOUT THE AUTHORS

Maria A. Lapina – Associate Professor of the Department of Computational Mathematics and Cybernetics of the North Caucasus Federal University, Stavropol, mlapina@ncfu.ru

Alexander V. Mitrichenko – Student of the North Caucasus Federal University, Stavropol, alekhandrodebruche@mail.ru

Egor A. Russkikh – Postgraduate Student of the Moscow Finance and Law Academy, Russkikh.egor77@yandex.ru

Patimat A. Ibragimova – Student of the North Caucasus Federal University, Stavropol, patimat.ibragimov4@yandex.ru

Alisa A. Kushchenko – Student of the North Caucasus Federal University, Stavropol, aliskushchenko@yandex.ru

Contribution of the authors: the authors contributed equally to this article.

Conflict of interest: the authors declares no conflicts of interests.

The article was submitted: 01.04.2025;

approved after reviewing: 12.05.2025;

accepted for publication: 01.06.2025.

ИНФОРМАЦИЯ ОБ АВТОРАХ

Мария Анатольевна Лапина – доцент кафедры вычислительной математики и кибернетики Северо-Кавказского федерального университета, Ставрополь, mlapina@ncfu.ru

Александр Вячеславович Митриченко – студент Северо-Кавказского федерального университета, Ставрополь, alekhandrodebruche@mail.ru

Егор Аркадьевич Русских – аспирант Московской финансово-юридической академии, Москва, Russkikh.egor77@yandex.ru

Патимат Абдуллаевна Ибрагимова – студент Северо-Кавказского федерального университета, Ставрополь, patimat.ibragimov4@yandex.ru

Алиса Андреевна Кущенко – студент Северо-Кавказского федерального университета, Ставрополь, alisakuschenko@yandex.ru

Вклад авторов: все авторы внесли равный вклад в подготовку публикации.

Конфликт интересов: авторы заявляют об отсутствии конфликта интересов.

Статья поступила в редакцию: 01.04.2025;
одобрена после рецензирования: 12.05.2025;
принята к публикации: 01.06.2025.